



BEVERAGE TRUCK TIRES



USE THIS QUICK REFERENCE GUIDE TO FIND THE RIGHT TIRE FOR YOUR APPLICATION.

Position Page Tire Size	All Position (Regional)					Drive (Regional)					Trailer
	Page 6	Page 7	Page 7	Page 8	Page 8	Page 9	Page 9	Page 10	Page 10	Page 11	Page 11
	6661 [®] HSA [™]	6949 RSA [™] Armor Max [®]	6662 [®] RSA [™] Fuel Max [®]	6647 RSS [®]	6947 RSS [™] Armor Max [®]	6182 RSD [®]	6622 RSD [®]	6633 RSD [™]	6933 RSD [™] Armor Max [®]	6971 [™] Armor Max [®]	6114 [™] LHT [™]
Light Truck	LT225/75R16	F			F				F		
	LT245/75R16	F			F				F		
	LT215/85R16	F			F				F	F	
	LT235/85R16	F			F				F	F	
Truck – Tubeless	9R17.5HC										H
	10R17.5										H
	8R19.5				F			F			
	9R22.5	F									
	10R22.5	G					G				
	11R22.5	G, H		G, H		G, H	H				
	12R22.5	H				H	H				
	11R24.5	G, H		H		G, H	G				
	12R24.5										
	215/75R17.5										H
	225/70R19.5	G		F, G			F, G				
	245/70R19.5	G		G			G				
	265/70R19.5										
	385/65R22.5										
	425/65R22.5										
	445/65R22.5										
	255/70R22.5	H					H				
	275/70R22.5	J									
	245/75R22.5	G					G				
	265/75R22.5	G					G				
295/75R22.5	G		G		G	G					
285/75R24.5											
Tube Type	10.00R15TR										
	10.00R20										
	11.00R20										
	11.00R22										
	11.00R24										
	12.00R24										
	315/80R22.5										

NOTE: The letters in the chart represent load ranges.
Wrangler Light Truck sizes available on pages 13 – 17.

GOODYEAR[®] COMMERCIAL TRUCK TIRES – INNOVATION FOR TODAY'S WORK TRUCKS.

Goodyear has been a leader in commercial truck tire technology for more than a century. As vehicles evolve and their capabilities and duties change, Goodyear works to create relevant technologies and adapt product lines for beverage trucks.

Goodyear is driven to develop tires that help deliver dependable performance. Getting to the job, getting around town and getting home – Goodyear is committed to helping you get the job done.



THE TOTAL SOLUTION FOR YOUR FLEETS.

Goodyear® can help you lower your operating costs and keep your fleet up and running.

Innovative Products: Choose from tires featuring advanced technologies

Best-In-Class Services: Count on our national dealer network for 24/7 support

Profitability Tools: Get the information you need to help save money with every mile

INNOVATIVE TECHNOLOGY THAT WORKS HARD FOR YOU.



The Toughness Of Armor Max® Technology.

Armor Max Technology offers light truck tires enhanced toughness from advanced compounds and construction. Plus you get long casing life and retreadability from steel-reinforced sidewalls to help you save money.

Less Downtime With DuraSeal Technology®.

DuraSeal Technology helps keep your trucks running by sealing up to ¼" tread punctures* again and again with its yellow gel-like rubber compound. That means no stopping for repairs and no downtime!

*Seals up to ¼" diameter punctures in the repairable area of the tread. Does not seal sidewall punctures.

Save Money With Fuel Max® Technology.

Fuel Max Technology helps improve your truck's miles per gallon with fuel-saving compounds and constructions. It's an innovation that can help you reduce your overall fuel costs with every mile you drive.

SAVE MONEY WITH GOODYEAR RETREADS.

Save Money Again And Again With Goodyear Retreads.

Goodyear retreads can help you save money and offer you like-new performance compared to the original treads. Plus, if your tires feature DuraSeal Technology, Fuel Max Technology or Armor Max Technology, you'll continue to enjoy the same benefits from your retreaded tires.

Goodyear retread services are available through a nationwide network of authorized Goodyear retreaders and dealers.

Goodyear offers the following types of innovative retreads:

- **UniCircle® Retreads** feature seamless construction and matching treads for enhanced casing life and mileage
- **Precure Retreads** feature matching tread designs for long-lasting performance



MANAGE YOUR FLEET. NOT YOUR TIRES.



Goodyear Fleet HQ® offers an array of premium benefits designed to help reduce your operating costs. These benefits go beyond tires and extend to the services and processes that make it easier to do business. In the past these advantages were available exclusively to the largest national fleets, but Goodyear Fleet HQ now makes them available to fleets of every size. Better yet, there is no cost to join and no fee to use Goodyear Fleet HQ.

The Tires You Want.

Dealers in the Goodyear Fleet HQ network have access to the full line of Goodyear commercial truck tires so they can provide you the tires that work best for your fleet!

The Services You Need.

Whether your fleet is large or small, Goodyear Fleet HQ can help by offering you access to national programs and tools that help you with tires and tire-related services. Solutions like Tire Trac, Gold Medallion and Goodyear Fleet HQ 24/7 Mobile Access offer you the flexibility to manage your fleet's tires and streamline your day-to-day operations.

Become A Goodyear Fleet HQ Preferred Fleet.

It doesn't matter if you need normal service during the day or emergency service in the middle of the night, Goodyear Fleet HQ pricing remains the same! Billings for products and services provided throughout the network are consolidated through your local Dealer. Visit your local Goodyear Fleet HQ Dealer to sign up for free and get access to the following solutions:

- 24/7/365 Emergency Roadside Service
- Billing through your Dealer even when outside your area
- Back office support
- Gold Medallion Retreaded Tires
- Tire Trac online tire management
- Goodyear Fleet HQ 24/7 Mobile Access

Premium Solutions To Help You Save Money.

Goodyear Fleet HQ Preferred Fleets can enjoy the money-saving benefits of premium solutions like Tire Trac, Gold Medallion Retreaded Tires and Goodyear Fleet HQ 24/7 Mobile Access. See which programs work for your fleet's individual needs!

Tire Trac – Information To Manage Your Tires.

Tire Trac is Goodyear Fleet HQ's powerful online tire management tool that informs you about the condition of your tires and helps you manage their performance for optimum value. You can closely track tire performance to evaluate whether you're using the right products and whether your maintenance program is on track.

Tire Trac information is just a click away:

- Tire purchase, retread and road service history
- Overall condition of all the tires in your fleet
- Comprehensive scrap analysis
- Fleet summary of wear conditions
- Cost of ownership and operation analysis



Gold Medallion – The New Gold Standard in Retreads.

With Gold Medallion, you can be confident knowing exactly what you're getting – a quality retreaded tire that meets your specs for drive and trailer positions. Just look for the "Gold" emblem branded into the side of the tread.



GOLD MEDALLION RETREADED TIRE

Goodyear Fleet HQ 24/7 Mobile Access – Help When You Need It.

With Goodyear Fleet HQ's 24/7 mobile service application, you can easily search for nearby service centers by clicking on your smart phone. Plus, our mobile service application allows a Goodyear Fleet HQ Dealer near you to rapidly identify your smart phone's GPS location to quickly dispatch road service. Goodyear Fleet HQ 24/7 Mobile Access is available for iPhone, Android and Blackberry.

ALL-POSITION (REGIONAL)

G661® HSA™ ENHANCED TOUGHNESS FOR HIGH-SCRUB APPLICATIONS.

- Scrub-resistant tread, with a multi-compound construction, helps extend tread life when used in local applications that require frequent turning, backing and braking.
- Four full-sized, super-tensile steel belts help reinforce the tread for enhanced toughness.
- Penetration protectors help resist cuts and punctures for enhanced toughness and long casing life.
- Sidewall protector ribs and a scrub-resistant compound help protect against sidewall abrasions from curbing.
- TredLock® Technology features interlocking microgrooves that help stabilize the tread for long tread life and enhanced toughness.
- Up to 22/32" tread depth helps deliver long original tread life.



Matching Retreads

Retreads	Size	Available Width in	Tread Depth 32nds
UniCircle®	285/75R22.5	8½, 9	17, 18
UniCircle	295/75R22.5	8½, 9	20
UniCircle	11R22.5	8½	20
UniCircle	11R24.5	8½, 9	20
Precure	—	8½, 9	20

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width in	Overall Width in	Overall Diameter in	Static Radius in	RPM	RPK	Tread Depth 32nds	Min. Dual Spacing in	Speed Rating				
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg													
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
9R22.5	F	4,540	2,060	105	720	4,300	1,950	105	720	96	44	6.75	9.1	231	38.7	983	18.2	462	537	334	18	10.3	262	75
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	112	51	7.50	10.1	257	40.4	1,026	18.9	480	514	319	21	11.4	290	75
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	126	57	8.25	10.8	274	41.8	1,062	19.5	495	497	309	22	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	126	57	8.25	10.8	274	41.8	1,062	19.5	495	497	309	22	12.5	318	75
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	140	64	9.00	11.6	294	42.9	1,090	20.1	511	484	301	22	13.5	343	75
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	64.0	29	6.75	8.7	221	32.3	820	15.0	381	643	400	17	10.0	254	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	73.1	33	6.75	9.6	244	33.3	846	15.5	394	625	388	18	11.0	279	75
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	97	44	7.50	10.0	254	36.7	932	17.2	437	566	352	18	11.3	287	81
275/70R22.5	J	6,940	3,150	130	900	6,395	2,900	130	900	105	48	7.50	10.5	267	38.0	965	17.7	450	547	340	19	11.9	302	75
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	91	41	7.50	9.5	241	36.7	932	17.3	439	566	352	19	11.0	279	75
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	100	690	102	46	7.50	10.0	254	38.5	978	18.1	460	539	334	20	11.6	295	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	122	55	8.25	11.3	287	40.6	1,031	19.0	483	512	318	22	12.9	328	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	135	61	8.25	11.0	279	43.6	1,107	20.3	516	476	296	22	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	135	61	8.25	11.0	279	43.6	1,107	20.3	516	476	296	22	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	124	56	8.25	11.2	284	41.8	1,062	19.7	500	497	309	22	12.5	318	75



G949 RSA™ ARMOR MAX® ENHANCED TOUGHNESS AND EVEN WEAR FOR HIGHWAY AND LOCAL APPLICATIONS.

- Advanced compounds and construction enhance toughness.
- Reinforced shoulders and steel sidewalls help deliver long casing life and retreadability.
- Tread pattern helps evacuate water from under the footprint to enhance traction on wet roads.
- Penetration protectors help resist cuts and punctures for enhanced toughness and long casing life.



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width in	Overall Width in	Overall Diameter in	Static Radius in	RPM	RPK	Tread Depth 32nds	Min. Dual Spacing in	Speed Rating				
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg													
TUBELESS TIRES ON 5" DROP CENTER RIMS																								
LT225/75R16	E	2,680	1,215	80	550	2,470	1,120	80	550	48	22	6.00	8.8	224	29.4	747	13.8	351	701	436	14	10.2	259	75
LT245/75R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	6.50	9.6	244	30.9	785	14.5	368	667	415	15	10.8	274	75
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	51	23	6.00	8.6	218	30.4	772	14.4	366	678	421	14	9.9	251	75
LT235/85R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	6.50	9.6	244	30.9	785	14.5	368	667	415	15	10.8	274	75



G662® RSA™ FUEL MAX® LONG TREAD LIFE AND TOUGHNESS FOR REGIONAL HIGHWAY AND LOCAL DRIVING.

- The 22/32" tread depth helps deliver long original tread life.
- Four full-sized, super-tensile steel belts help reinforce the tread for enhanced toughness.
- Pressure distribution groove helps direct pressure away from the shoulder for uniform treadwear and long tread life.
- TredLock® Technology features interlocking microgrooves that help stabilize the tread for long tread life and enhanced toughness.
- Fuel Max® Technology, with a multi-compound construction, helps reduce the amount of energy generated within the tread for lower rolling resistance that enhances fuel efficiency on the highway while maintaining long tread life.



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width in	Overall Width in	Overall Diameter in	Static Radius in	RPM	RPK	Tread Depth 32nds	Min. Dual Spacing in	Speed Rating				
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg													
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	123	56	8.25	10.8	274	41.8	1,062	19.5	495	497	309	22	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	124	56	8.25	10.8	274	41.8	1,062	19.5	495	497	309	22	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	123	56	8.25	11.3	287	40.6	1,031	19.0	483	512	318	22	12.9	328	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	133	60	8.25	10.8	274	43.6	1,107	20.5	521	476	296	22	12.5	318	75



ALL-POSITION (REGIONAL)

G647 RSS® SUPERB CHOICE FOR HIGH-SCRUB APPLICATIONS.

- Suggested for extremely fast wear rate applications, such as package delivery.
- Tread compound for high-scrub service.
- Circumferential grooves and lateral blades help provide superb wet traction.
- Raised sidewall protector ribs help resist sidewall scuffing.
- Sidewall wear indicators help give early warning of wear due to excessive scuffing.
- Tread radius helps resist fast wear and tread scrubbing from frequent turns.
- M+S stamped because the tread design helps deliver traction in dry, wet, muddy and snowy conditions.

Matching Retreads

Retreads	Size	Available Width in	Tread Depth 32nds
UniCircle®	225/70R19.5	7½	16
UniCircle	245/75R19.5	8½	16
Precure	-	7, 7½, 7¾, 8, 8½	16

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing in	Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm					
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
225/70R19.5	F	3,640	1,600	95	660	3,415	1,550	95	660	63	29	6.75	8.9	226	32.2	818	15.0	381	640	398	16	10.0	254	75
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	65	29	6.75	8.9	226	32.2	818	15.0	381	640	398	16	10.0	254	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	75	34	7.50	9.5	242	33.2	845	15.4	392	626	389	16.5	11.0	280	75
8R19.5	F	3,525	1,600	110	760	3,415	1,550	110	760	59	27	6.00	8.3	211	33.3	846	15.6	396	619	385	13	9.3	236	75



DRIVE (REGIONAL)

G182 RSD® ALL-AROUND TIRE FOR REGIONAL SERVICE.

- Non-directional tread design for uniform footprint.
- Enhanced rubber volume means many miles to removal.
- Open lug design helps provide traction in wet or snowy conditions.
- Tie-bar shoulder and bladed tread pattern help deliver long, even wear.
- Deep 28/32" tread depth helps enhance traction.

Matching Retreads

Retreads	Size	Available Width in	Tread Depth 32nds
UniCircle®	295/75R22.5	8½, 9	28
UniCircle	11R22.5	8½, 9	28
UniCircle	285/75R24.5	8½, 9	28
UniCircle	11R24.5	8½	28
Precure	-	8", 8½", 9", 9½"	26

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing in	Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm					
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	134	61	8.25	10.8	274	42.1	1,069	19.6	498	496	308	28	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	133	60	8.25	10.8	274	42.1	1,069	19.6	498	496	308	28	12.5	318	75
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	150	68	9.00	11.7	297	43.4	1,102	20.4	518	481	299	28	13.5	343	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	122	55	8.25	11.3	287	40.8	1,036	19.0	483	512	318	28	12.9	328	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	143	65	8.25	11.0	279	44.1	1,120	20.8	528	473	294	28	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	142	64	8.25	11.0	279	44.1	1,120	20.8	528	473	294	28	12.5	318	75

*Tread design also available with sipes.



G947 RSS™ ARMOR MAX® ENHANCED TOUGHNESS FOR HIGH-SCRUB APPLICATIONS.

- Advanced compounds and construction enhance toughness.
- Reinforced shoulders and steel-reinforced sidewalls help deliver long casing life and retreadability.
- Compound and tread design help promote long tread life and strong performance for curbside parking when used on local streets.
- M+S stamped because the tread design helps deliver traction in dry, wet, muddy and snowy conditions.
- Sidewall protector ribs help resist sidewall scuffing from turning, backing and braking when used in local neighborhoods.
- Sidewall wear indicators help give early warning of wear due to excessive scuffing.



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing in	Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm					
TUBELESS TIRES ON 5" DROP CENTER RIMS																								
LT225/75R16	E	2,680	1,215	80	550	2,470	1,120	80	550	50	23	6.00	8.8	224	29.4	747	13.7	348	701	436	14	10.2	259	75
LT245/75R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	6.50	9.7	246	30.9	785	14.4	366	667	415	15	10.8	274	75
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	51	23	6.00	8.7	221	30.4	772	14.2	361	678	421	14	9.9	251	75
LT235/85R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	6.50	9.7	246	30.9	785	14.4	366	667	415	15	10.8	274	75



G622 RSD® FOR REGIONAL AND LOCAL HIGH-SCRUB APPLICATIONS.

- Aggressive blading helps provide outstanding traction.
- Tie-barred shoulders enhance handling and help deliver even wear.
- Increased wearable tread rubber helps enhance mileage.
- Unisteel® construction enhances toughness and retreadability.

Matching Retreads

Retreads	Size	Available Width in	Tread Depth 32nds
UniCircle®	225/70R19.5	7½	20
UniCircle	245/70R19.5	8½	19
UniCircle	11R22.5	8½, 9	26
UniCircle	295/75R22.5	8½, 9	26
UniCircle	11R24.5	8½	26
Precure	-	7, 7½, 8, 8½, 8¾, 9¼	22
Precure	-	7, 7½, 8, 8½	16

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing in	Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm					
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
225/70R19.5	F	3,640	1,650	95	660	3,415	1,550	95	660	63	28	6.75	8.9	226	32.4	824	15.1	384	641	398	19	10.0	254	75
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	65	29	6.75	8.9	226	32.4	824	15.1	384	641	398	19	10.0	254	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	75	34	7.50	9.7	245	33.5	852	15.6	397	620	389	19	11.0	280	75
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	112	51	7.50	10.2	259	40.6	1,031	19.0	483	512	318	23	11.4	290	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	128	58	8.25	11.1	282	42.0	1,067	19.7	500	497	309	26	12.5	318	75
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	139	63	9.00	11.7	297	43.3	1,100	20.3	516	482	300	22	13.5	343	75
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	96	44	7.50	10.0	254	37.0	940	17.3	439	561	349	23	11.3	287	81
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	94	43	7.50	9.6	244	37.6	955	17.7	450	552	343	23	11.0	279	75
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	110	760	102	47	7.50	10.0	254	38.9	988	18.3	465	561	349	23	11.6	295	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	118	54	8.25	11.2	284	40.8	1,036	19.1	485	512	318	26	12.9	328	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	135	61	8.25	11.1	282	43.9	1,115	20.6	523	475	295	26	12.5	318	75



DRIVE (REGIONAL)

G633 RSD™ TRACTION-BLOCK TREAD PATTERN FOR THE REGIONAL DRIVE POSITION.

- Traction-block design offers high drive wheel efficiency.
- Blading pattern enhances traction in mud, snow and rain.
- High-tensile steel casing and belt construction help provide toughness, retreadability and puncture resistance.
- Tough rubber compounds help resist excessive wear, chunking, cracking and chipping.



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15" DROP CENTER RIMS																									
8R19.5	F	3,525	1,600	110	760	3,415	1,550	110	760	60	27	6.00	8.1	206	33.4	848	15.6	396	622	387	16	9.1	231	75	



G971™ ARMOR MAX® ENHANCED TOUGHNESS FOR MINING, LOGGING AND RAIL YARD APPLICATIONS.

- Advanced compounds and construction enhance toughness.
- Reinforced shoulders and steel sidewalls help deliver long casing life and retreadability.
- Tread compound helps resist chipping, chunking and tearing for toughness and long casing life.
- Tread design offers enhanced off-road traction.
- Heavy undertread enhances retreadability and helps protect against belt damage.



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 5" DROP CENTER RIMS																									
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	51	23	6.00	8.6	218	30.8	782	14.4	366	674	419	17	9.9	251	75	
LT235/85R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	6.50	9.5	241	31.1	790	14.5	368	668	415	18	10.8	274	75	



G933 RSD™ ARMOR MAX® ENHANCED TOUGHNESS AND ALL-SEASON TRACTION ON LOCAL STREETS AND INTERSTATE HIGHWAYS.

- Advanced compounds and construction enhance toughness.
- Reinforced shoulders and steel sidewalls help deliver long casing life and retreadability.
- Aggressive blading helps provide road-gripping traction.
- M+S stamped because the tread design helps deliver traction in dry, wet, muddy and snowy conditions.



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 5" DROP CENTER RIMS																									
LT225/75R16	E	2,680	1,215	80	550	2,470	1,120	80	550	49	22	6.00	8.8	224	29.5	749	13.8	351	699	434	16	10.2	259	75	
LT245/75R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	6.50	9.5	241	31.0	787	14.4	366	665	413	16	10.8	274	75	
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	51	23	6.00	8.6	218	30.5	775	14.2	361	676	420	16	9.9	251	75	
LT235/85R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	6.50	9.5	241	31.0	787	14.4	366	665	413	16	10.8	274	75	



TRAILER

G114™ LHT™ LONG, EVEN-WEARING TIRE FOR FREE-ROLLING WHEEL POSITIONS.

- Solid, rounded shoulder ribs enhance rib stability to promote even wear.
- Deep, five-rib tread design enhances lateral traction on wet and dry surfaces.



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15" DROP CENTER RIMS																									
9R17.5HC	H	4,410	2,000	110	760	4,190	1,900	110	760	77	35	6.75	8.9	226	33.3	846	15.4	391	619	385	14	10.3	262	75	
10R17.5	H	4,675	2,120	115	800	4,410	2,000	115	800	73	33	6.75	9.4	239	33.7	856	15.6	396	612	380	14	10.9	277	75	
215/75R17.5	H	4,805	2,180	125	860	4,540	2,060	125	860	62	28	6.75	8.8	224	30.5	775	14.2	361	676	420	16	10.0	254	75	



LIGHT TRUCK

WRANGLER® ALL-TERRAIN ADVENTURE WITH KEVLAR® PRO-GRADE OUR MOST VERSATILE ALL-TERRAIN TIRE WITH THE TOUGHNESS OF DUPONT™ KEVLAR® TO GO OFF-ROAD AT A MOMENT'S NOTICE.

- A layer of Dupont™ Kevlar® and exclusive Durawall™ Technology offers rugged strength for confident off-road driving and helps resist cuts and punctures
- Traction ridges and open shoulder blocks help clear mud and snow for versatile off-road traction
- Biting edges and a rubber compound offering superior traction on wet and icy roads
- 20% longer tread life limited warranty† (60,000 Miles/95,000 kilometres*)
- Pro-Grade package on LT sizes featuring two layers of Kevlar®, belts with 30% more steel‡ and marked with the Severe Snow Conditions Symbol**

†Compared to other Wrangler tires.

‡Compared to standard load tires.

*See warranty brochure for complete details.

**LT sizes only

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.



Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Width (ins)	Measuring Rim Width (ins)	Section Width (ins)	Overall Diameter (ins)	Max Load (lbs)	Tread Depth (In 32nds)	Revs/ Mile
31X10.50R15LT*	109R	C	OWL	748510571	219161	7.0 - 9.0	8.5	10.6	30.8	2,270	15	681
LT215/85R16	115R	E	BSL	748517572	219162	5.5 - 7.0	6.0	8.6	30.5	2,680	15	688
LT225/75R16	115R	E	BSL	748748572	219159	6.0 - 7.0	6.0	8.8	29.3	2,680	15	714
LT235/85R16	120R	E	BSL	748745572	219158	6.0 - 7.5	6.5	9.3	31.7	3,042	15	659
LT245/75R16	120S	E	BSL	748103572	225437	6.5 - 8.0	7.0	9.8	30.5	3,042	15	686
LT245/75R16	120S	E	OWL	748103571	225438	6.5 - 8.0	7.0	9.8	30.5	3,042	15	686
LT265/75R16	123R	E	BSL	748746572	219157	7.0 - 8.0	7.5	10.5	31.7	3,415	15	660
LT265/75R16	123R	E	OWL	748746571	220325	7.0 - 8.0	7.5	10.5	31.7	3,415	15	660
LT285/75R16	126R	E	OWL	748585571	219166	7.5 - 9.0	8.0	11.3	32.8	3,750	15	637
LT285/75R16	126R	E	BSL	748585572	220328	7.5 - 9.0	8.0	11.3	32.8	3,750	15	637
LT235/80R17	120R	E	BSL	748635572	219165	6.0 - 7.5	6.5	9.3	31.8	3,085	15	654
LT245/70R17	119R	E	OWL	748469571	219169	6.5 - 8.0	7.0	9.8	30.6	3,000	15	684
LT245/70R17	119R	E	BSL	748469572	220329	6.5 - 8.0	7.0	9.8	30.6	3,000	15	684
LT245/75R17	121S	E	OWL	748104571	225439	6.5 - 7.5	7.0	9.8	31.5	3,195	15	663
LT245/75R17	121S	E	BSL	748104572	225440	6.5 - 7.5	7.0	9.8	31.5	3,195	15	663
LT265/70R17	121S	E	OWL	748661571	225841	7.0 - 8.5	8.0	10.7	31.7	3,195	15	660
LT265/70R17	121S	E	BSL	748661572	225843	7.0 - 8.5	8.0	10.7	31.7	3,195	15	660
LT285/70R17	121R	E	OWL	748096571	219170	7.5 - 9.0	8.5	11.5	32.8	3,195	15	638
LT285/70R17	121R	E	BSL	748096572	220330	7.5 - 9.0	8.5	11.5	32.8	3,195	15	638
LT265/70R18	124S	E	BSL	748014572	225842	7.0 - 9.0	8.0	10.7	32.6	3,527	15	638
LT275/65R18	123S	E	OWL	748965571	225844	7.5 - 9.0	8.0	11.0	32.1	3,415	15	651
LT275/70R18	125S	E	BSL	748108572	225461	7.0 - 8.5	8.0	11.0	33.2	3,640	15	630
LT275/70R18	125S	E	OWL	748108571	225462	7.0 - 8.5	8.0	11.0	33.2	3,640	15	630
LT285/65R18	125R	E	BSL	748093572	220338	8.0 - 10.0	8.5	11.5	32.6	3,640	15	639
LT265/60R20	121R	E	BSL	748097572	220332	7.5 - 9.5	8.0	10.7	32.5	3,197	15	640
LT275/65R20	126S	E	OWL	748303571	226061	7.5 - 9.5	8.0	11.0	34.1	3,750	15	610
LT275/65R20	126S	E	BSL	748303572	226062	7.5 - 9.5	8.0	11.0	34.1	3,750	15	610
LT285/55R20	122R	E	BSL	748101572	220336	8.0 - 10.0	9.0	11.7	32.4	3,305	15	646
LT285/60R20	125R	E	BSL	748015572	220337	8.0 - 10.0	8.5	11.5	33.5	3,638	15	622
LT305/55R20	121R	E	BSL	748094572	219173	8.5 - 11.0	9.5	12.4	33.2	3,195	15	622

*Wrangler All-Terrain Adventure with Kevlar®

WRANGLER MT/R® WITH KEVLAR® THE REVOLUTIONARY OFF-ROAD TIRE BUILT WITH THE RUGGED TOUGHNESS OF DUPONT™ KEVLAR® FOR ENHANCED SIDEWALL PUNCTURE RESISTANCE.

- DuPont™ Kevlar® reinforced sidewalls help increase sidewall puncture resistance by 35% for confidence in tough terrain.*
- Hardworking wraparound tread offers enhanced sidewall traction in deep mud, sand and rocks.
- Innovative asymmetric tread design offers aggressive off-road traction while maintaining enhanced handling on the road.
- Advanced silica rubber for superb off-road and wet traction.

*Source: Goodyear Sidewall Penetration Energy – LT285/70R17 LR-D 65 psi.

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.



Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Width (ins)	Measuring Rim Width (ins)	Section Width (ins)	Overall Diameter (ins)	Max Load (lbs)	Tread Depth (In 32nds)	Revs/ Mile
31X10.50R15LT	109Q	C	BSL	750710326	219336	7.0 - 9.0	8.5	10.6	30.8	2,270	19	681
32X11.50R15LT	113Q	C	BSL	750732326	219346	8.0 - 10.0	9.0	11.4	31.8	2,535	21	655
33X12.50R15LT	108Q	C	BSL	750711326	219335	8.5 - 11.0	10.0	12.5	32.8	2,205	21	635
35X12.50R15LT	113Q	C	BSL	750712326	208009	8.5 - 11.0	10.0	12.5	34.8	2,535	21	598
LT235/85R16	120Q	E	BSL	750713326	208010	6.0 - 7.5	6.5	9.3	31.7	3,042	18	659
LT245/75R16	120Q	E	BSL	750151326	219334	6.5 - 8.0	7.0	9.8	30.7	3,042	18	686
LT265/75R16	123Q	E	BSL	750153326	219332	7.0 - 8.0	7.5	10.5	31.7	3,415	18	660
LT285/75R16	126Q	E	BSL	750451326	219333	7.5 - 9.0	8.0	11.3	33.1	3,750	18	637
LT305/70R16	124Q	E	BSL	750475326	219344	8.0 - 9.5	9.0	12.2	33.1	3,525	18	637
LT315/75R16	121Q	D	BSL	750554326	207999	8.0 - 10.0	8.5	12.3	34.8	3,195	21	598
LT245/70R17	119Q	E	BSL	750140326	219342	6.5 - 8.0	7.0	9.8	30.6	3,000	18	684
LT245/75R17	121Q	E	BSL	750707326	219339	6.5 - 7.5	7.0	9.8	31.7	3,195	18	663
LT255/75R17	111Q	C	BSL	750687326	208560	6.5 - 8.5	7.0	10.0	32.3	2,405	19	644
LT265/70R17	121Q	E	BSL	750152326	219331	7.0 - 8.5	8.0	10.7	31.7	3,195	18	660
LT275/70R17	121Q	E	BSL	750393326	219349	7.0 - 8.5	8.0	11.0	32.4	3,195	18	649
LT285/70R17	121Q	D	BSL	750434326	219280	7.5 - 9.0	8.5	11.5	33.0	3,195	19	638
LT305/70R17	119Q	D	BSL	750542326	219337	8.0 - 9.5	9.0	12.2	34.1	3,000	19	617
LT315/70R17	121Q	D	BSL	750551326	219340	8.5 - 10.0	9.5	12.7	34.7	3,195	21	607
35X12.50R17LT	111Q	C	BSL	750740326	208003	8.5 - 11.0	10.0	12.5	34.8	2,405	21	598
37X12.50R17LT	124Q	D	BSL	750578326	208000	8.5 - 11.0	10.0	12.5	36.8	3,525	21	566
38X14.50R17LT	121Q	D	BSL	750736326	208013	10.0 - 12.0	12.0	14.7	37.8	3,195	21	551
40X13.50R17LT	121Q	C	BSL	750622326	208001	8.5 - 11.0	11.0	13.6	39.8	3,195	21	523
42X14.50R17LT	121Q	C	BSL	750625326	208002	10.0 - 12.0	12.0	14.7	41.8	3,195	21	496
LT275/65R18	113Q	C	BSL	750392326	219348	7.5 - 9.0	8.0	11.0	32.1	2,535	19	651
LT275/70R18	125Q	E	BSL	750432326	219338	7.0 - 8.5	8.0	11.0	33.4	3,640	18	630
LT285/75R18	129Q	E	BSL	750485326	207995	7.5 - 9.5	8.0	11.3	35.1	4,080	18	593
35X12.50R18LT	123Q	E	BSL	750032326	216875	8.5 - 11.0	10.0	12.5	34.8	3,415	18	598
LT275/65R20	126Q	E	BSL	750714326	208011	7.5 - 9.5	8.0	11.0	34.1	3,750	18	610
LT285/65R20	127Q	E	BSL	750435326	207993	8.0 - 10.0	8.5	11.5	34.8	3,860	18	598
33X12.50R20LT	114Q	E	BSL	750035326	216879	8.5 - 11.0	10.0	12.5	32.8	2,600	18	633
35X12.50R20LT	121Q	E	BSL	750002326	216874	8.5 - 11.0	10.0	12.5	34.8	3,195	18	598

LIGHT TRUCK

WRANGLER DURATRAC®

A HARDWORKING, VERSATILE TIRE OFFERING ON- AND OFF-ROAD TRACTION.

- TractiveGroove Technology® offers enhanced traction in deep mud and snow.
- Self-cleaning shoulder blocks help provide enhanced dirt, gravel and mud traction.
- Highly angled center tread blocks help provide enhanced traction and lateral stability while reducing road noise.
- Rim protector helps protect wheels from accidental curb damage.
- Pinned for #16 metal studs* for enhanced traction in winter driving conditions.



*Consult state and provincial laws regarding stud use. Use stud #16.

Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Width (ins)	Measuring Rim Width (ins)	Section Width (ins)	Overall Diameter (ins)	Max Load (lbs)	Tread Depth (In 32nds)	Revs/ Mile
LT235/75R15	104Q	C	OWL	312008027	208387	6.0 - 7.0	6.5	9.3	28.9	1,985	18	724
31X10.50R15LT	109Q	C	OWL	312007027	208386	7.0 - 9.0	8.5	10.6	30.8	2,270	18	681
33X12.50R15LT	108Q	C	OWL	312020027	208399	8.5 - 11.0	10.0	12.5	32.8	2,205	18	635
LT215/85R16	115Q	E	BSL	312010142	208389	5.5 - 7.0	6.0	8.6	30.5	2,680	18	688
LT225/75R16	115Q	E	BSL	312009142	208388	6.0 - 7.0	6.0	8.8	29.3	2,680	18	714
LT235/85R16	120Q	E	BSL	312036142	220217	6.0 - 7.5	6.5	9.3	31.7	3,042	18	659
LT245/75R16	120Q	E	OWL	312249027	208316	6.5 - 8.0	7.0	9.8	30.7	3,042	18	686
LT245/75R16	108Q	C	OWL	312017027	208396	6.5 - 8.0	7.0	9.8	30.7	2,205	18	686
LT265/75R16	112Q	C	OWL	312018027	208414	7.0 - 8.0	7.5	10.5	31.7	2,470	18	660
LT265/75R16	123Q	E	BSL	312034142	223558	7.0 - 8.0	7.5	10.5	31.7	3,415	18	660
LT285/75R16	126P	E	OWL	312035027	220216	7.5 - 9.0	8.0	11.3	33.1	3,750	18	637
LT285/75R16	126P	E	BSL	312035142	223557	7.5 - 9.0	8.0	11.3	33.1	3,750	18	637
LT305/70R16	124Q	E	BSL	312037142	220315	8.0 - 9.5	9.0	12.2	33.1	3,525	18	637
LT315/75R16	127Q	E	BSL	312013142	208392	8.0 - 10.0	8.5	12.3	34.8	3,860	18	605
LT235/80R17	120Q	E	BSL	312032142	216880	6.0 - 7.5	6.5	9.3	31.8	3,085	18	654
LT245/70R17	119Q	E	BSL	312022142	208401	6.5 - 8.0	7.0	9.8	30.6	3,000	18	684
LT245/75R17	121Q	E	OWL	312023027	208347	6.5 - 7.5	7.0	9.8	31.7	3,195	18	663
LT265/70R17	121Q	E	BSL	312014142	208393	7.0 - 8.5	8.0	10.7	31.7	3,195	18	660
LT265/70R17	112Q	C	OWL	312019027	208398	7.0 - 8.5	8.0	10.7	31.7	2,470	18	660
LT285/70R17	121Q	D	OWL	312015027	208394	7.5 - 9.0	8.5	11.5	33.0	3,195	18	638
LT315/70R17	121Q	D	BSL	312031142	208413	8.5 - 10.0	9.5	12.7	34.4	3,195	18	607
LT275/65R18	123Q	E	BSL	312011142	208390	7.5 - 9.0	8.0	11.0	32.1	3,415	18	651
LT275/70R18	125Q	E	BSL	312012142	208391	7.0 - 8.5	8.0	11.0	33.4	3,640	18	630
LT295/65R18	127P	E	BSL	312024142	208348	8.0 - 10.0	8.5	11.8	33.1	3,860	18	624
LT325/65R18	127Q	E	BSL	312016142	208395	9.0 - 12.0	9.5	13.0	34.8	3,860	18	597
255/55R19	111S	XL	BLT	150663574	223967	7.0 - 9.0	8.0	10.4	30.0	2,403	16	696
LT275/65R20	126Q	E	BSL	312025142	208349	7.5 - 9.5	8.0	11.0	34.1	3,750	18	610
LT285/60R20	125Q	E	BSL	312028142	208350	8.0 - 10.0	8.5	11.5	33.5	3,640	18	622
LT305/55R20	121Q	E	BSL	312030142	208412	8.5 - 11.0	9.5	12.4	33.2	3,195	18	622
LT325/60R20	126Q	E	BSL	312029142	208411	9.0 - 12.0	9.5	13.0	35.6	3,750	18	584

WRANGLER SR-A®

WETTRAC® TECHNOLOGY FOR CONFIDENT WET TRACTION, ALL-TERRAIN CAPABILITIES AND A QUIET RIDE.

- Zigzag microgrooves offer enhanced traction in rain, snow and ice.
- Wide circumferential grooves help move water away from the tread for enhanced traction in rain.
- Exclusive wet traction compound helps provide traction on wet roads.



Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Width (ins)	Measuring Rim Width (ins)	Section Width (ins)	Overall Diameter (ins)	Max Load (lbs)	Tread Depth (In 32nds)	Revs/ Mile
P215/75R15	100S	SL	OWL	183025418	201206	5.5 - 7.0	6.0	8.5	27.7	1,742	11	755
P225/70R15	100S	SL	OWL	183482418	201530	6.0 - 7.5	6.5	9.0	27.4	1,753	11	762
P225/75R15	102S	SL	OWL	183064418	201207	6.0 - 7.5	6.0	8.8	28.3	1,874	11	738
P235/70R15	102S	SL	OWL	183408418	201205	6.0 - 8.0	7.0	9.5	28.0	1,896	11	747
†P235/75R15	105S	SL	OWL	183408418	198599	6.0 - 8.0	6.5	9.3	28.9	2,028	13	724
P265/70R15	110S	SL	OWL	183050418	201193	7.0 - 9.0	8.0	10.7	29.7	2,337	12	705
P265/75R15	112S	SL	OWL	183753418	201209	7.0 - 9.0	7.5	10.5	30.7	2,469	12	681
31X10.50R15LT	109R	C	OWL	179510492	203213	7.0 - 9.0	8.5	10.6	30.5	2,270	14	685
215/70R16	100S	SL	VSBL	183021436	216831	5.5 - 7.0	6.5	8.7	27.9	1,764	11	749
LT215/85R16	115P	E	BSL	179751217	212692	5.5 - 7.0	6.0	8.6	30.5	2,680	14	688
225/70R16	103T	SL	OWL	183054418	212665	6.0 - 7.5	6.5	9.0	28.4	1,819	11	736
LT225/75R16	115R	E	BSL	179748217	202632	6.0 - 7.0	6.0	8.8	29.3	2,680	14	714
P225/75R16	104S	SL	OWL	183017418	203073	6.0 - 7.5	6.0	8.8	29.3	1,984	11	714
†P235/70R16	104S	SL	OWL	183407418	135299	6.0 - 8.0	7.0	9.5	29.0	1,984	13	721
P235/75R16	109S	XL	OWL	183680418	201722	6.0 - 8.0	6.5	9.3	29.8	2,271	11	700
LT235/85R16	120R	E	BSL	179745217	202633	6.0 - 7.5	6.5	9.3	31.7	3,042	14	659
P245/70R16	106S	SL	VSBL	183293436	193621	6.5 - 8.0	7.0	9.8	29.5	2,094	12	708
P245/70R16	106S	SL	OWL	183597418	117875	6.5 - 8.0	7.0	9.8	29.5	2,094	13	708
LT245/75R16	120R	E	OWL	179747492	202634	6.5 - 8.0	7.0	9.8	30.5	3,042	14	686
LT245/75R16	120R	E	BSL	179747217	212693	6.5 - 8.0	7.0	9.8	30.5	3,042	13	686
P245/75R16	109S	SL	VSBL	183217436	199745	6.5 - 8.0	7.0	9.8	30.5	2,271	12	686
P245/75R16	109S	SL	OWL	183217418	201232	6.5 - 8.0	7.0	9.8	30.5	2,271	11	686
P255/65R16	106S	SL	OWL	183987418	201194	7.0 - 9.0	7.5	10.2	29.1	2,094	11	719
P255/70R16	109S	SL	OWL	183601418	201210	6.5 - 8.5	7.5	10.2	30.1	2,271	12	695
P265/70R16	111S	SL	OWL	183212418	201231	7.0 - 9.0	8.0	10.7	30.6	2,403	12	682
LT265/75R16	123R	E	OWL	179746492	202635	7.0 - 8.0	7.5	10.5	31.7	3,415	14	660
P265/75R16	114S	SL	OWL	183857418	201233	7.0 - 9.0	7.5	10.5	31.7	2,601	12	660
LT285/75R16	126R	E	OWL	179585492	202636	7.5 - 9.0	8.0	11.3	32.8	3,750	14	637
P215/65R17	98S	SL	OWL	183678418	201170	6.0 - 7.5	6.5	8.7	28.0	1,653	10	746
†P235/65R17	103S	SL	OWL	183105418	150861	6.5 - 8.5	7.0	9.5	29.1	1,929	13	719
P235/70R17	108S	XL	OWL	183783418	203075	6.0 - 8.0	7.0	9.5	30.0	2,205	11	693
P235/75R17	108S	SL	OWL	183539418	212666	6.0 - 8.0	6.5	9.3	30.9	2,205	11	677
LT235/80R17	120R	E	VSBL	179136436	166228	6.0 - 7.5	6.5	9.3	31.8	3,085	14	654
P245/65R17	105S	SL	OWL	183284418	193001	7.0 - 8.5	7.0	9.8	29.5	2,039	12	708
LT245/70R17	119R	E	OWL	179469492	203028	6.5 - 8.0	7.0	9.8	30.6	3,000	14	684
P245/70R17	108S	SL	VSBL	183114470	189903	6.5 - 8.0	7.0	9.8	30.6	2,205	11	684
LT245/75R17	121R	E	OWL	179636492	203029	6.5 - 7.5	7.0	9.8	31.5	3,195	14	663
P255/65R17	108S	SL	OWL	183579418	203074	7.0 - 9.0	7.5	10.2	30.1	2,205	11	691
P255/70R17	110S	SL	OWL	183540418	212667	6.5 - 8.5	7.5	10.2	31.1	2,337	12	672
†P255/75R17	113S	SL	OWL	183107418	199747	6.5 - 8.5	7.0	10.0	32.1	2,535	12	649
P265/65R17	110S	SL	VSBL	183602436	188100	7.5 - 9.5	8.0	10.7	30.6	2,337	11	684
P265/65R17	110S	SL	OWL	183952418	188025	7.5 - 9.5	8.0	10.7	30.6	2,337	11	684
LT265/70R17	121S	E	BSL	179696217	202212	7.0 - 8.5	8.0	10.7	31.7	3,195	15	660
LT265/70R17	121R	E	OWL	179535492	203076	7.0 - 8.5	8.0	10.7	31.7	3,195	14	660
P265/70R17	113R	SL	OWL	183106418	175026	7.0 - 9.0	8.0	10.7	31.7	2,535	12	660
P265/70R17	113R	SL	VSBL	183106436	175021	7.0 - 9.0	8.0	10.7	31.7	2,535	12	660
245/60R18	105T	SL	VSBL	183001436	216832	7.0 - 8.5	7.0	9.8	29.6	2,039	11	707
P255/70R18	112T	SL	OWL	183612418	212668	6.5 - 8.5	7.5	10.2	32.1	2,469	12	651
P265/60R18	109T	SL	VSBL	183558436	201944	7.5 - 9.5	8.0	10.7	30.5	2,271	11	682
P265/65R18	112T	SL	BSL	183051217	218920	7.5 - 9.5	8.0	10.7	31.5	2,469	12	663
P265/65R18	112S	SL	OWL	183055418	212669	7.5 - 9.5	8.0	10.7	31.5	2,469	11	663
P265/65R18	112T	SL	OWL	183051492	218962	7.5 - 9.5	8.0	10.7	31.5	2,469	12	663
LT265/70R18	124S	E	VSBL	179014436	214116	7.0 - 9.0	8.0	10.7	32.6	3,525	11	638
LT265/70R18	124S	E	VSBL	179040436	223022	7.0 - 9.0	8.0	10.7	32.6	3,525	13	638
P265/70R18	114S	SL	OWL	183487418	188898	7.0 - 9.0	8.0	10.7	32.6	2,601	11	640
LT275/65R18	123Q	E	OWL	179029492	216833	7.5 - 9.0	8.0	11.0	32.1	3,415	14	651
P275/65R18	114T	SL	OWL	183538418	204966	7.5 - 9.5	8.0	11.0	32.1	2,601	13	651
LT275/70R18	125R	E	OWL	179646492	212691	7.0 - 8.5	8.0	11.0				

LIGHT TRUCK

WRANGLER® ARMORTRAC™

AN ON- AND OFF-ROAD TIRE WITH AN ENHANCED TREAD FOR TOUGHNESS AND CONFIDENT TRACTION.

- Enhanced tread offers toughness in on- and off-road conditions.
- Jagged tread blocks help provide traction in wet conditions and enhance lateral stability.
- Open tread pattern helps provide off-road traction.
- Rim protector helps protect wheels against accidental curb damage.



Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Width (ins)	Measuring Rim Width (ins)	Section Width (ins)	Overall Diameter (ins)	Max Load (lbs)	Tread Depth (In 32nds)	Revs/Mile
P225/70R15	100T	SL	OWL	741734334	212741	6.0 - 7.5	6.5	9.0	27.4	1,753	13	762
P225/75R15	102T	SL	OWL	741490334	212742	6.0 - 7.5	6.0	8.8	28.3	1,874	13	738
P235/75R15	108T	XL	OWL	741507334	212743	6.0 - 8.0	6.5	9.3	28.9	2,183	13	724
P235/70R16	104T	SL	OWL	741492334	212744	6.0 - 8.0	7.0	9.5	29.0	1,984	13	721
P235/75R16	109T	XL	OWL	741022334	212747	6.0 - 8.0	6.5	9.3	29.8	2,271	13	700
P245/70R16	106T	SL	OWL	741495334	212745	6.5 - 8.0	7.0	9.8	29.5	2,094	13	708
LT245/75R16	120R	E	BSL	742747333	212708	6.5 - 8.0	7.0	9.8	30.5	3,042	15	686
P245/75R16	109T	SL	OWL	741496334	212748	6.5 - 8.0	7.0	9.8	30.5	2,271	13	686
P265/70R16	111T	SL	OWL	741500334	212746	7.0 - 9.0	8.0	10.7	30.6	2,403	13	682
LT265/75R16	123R	E	OWL	742746334	212709	7.0 - 8.0	7.5	10.5	31.7	3,415	16	660
P265/75R16	114T	SL	OWL	741503334	212749	7.0 - 9.0	7.5	10.5	31.7	2,601	13	660
P245/65R17	105T	SL	BSL	741494333	212750	7.0 - 8.5	7.0	9.8	29.5	2,039	13	708
P245/70R17	108T	SL	BSL	741508333	217020	6.5 - 8.0	7.0	9.8	30.6	2,205	13	684
LT245/75R17	121R	E	OWL	742636334	218227	6.5 - 7.5	7.0	9.8	31.5	3,195	15	663
LT265/70R17	121R	E	OWL	742535334	212710	7.0 - 8.5	8.0	10.7	31.7	3,195	16	660
P265/70R17	113T	SL	OWL	741501334	212751	7.0 - 9.0	8.0	10.7	31.7	2,535	13	660
P255/70R18	112T	SL	OWL	741612334	218226	6.5 - 8.5	7.5	10.2	32.1	2,469	13	651
P265/60R18	109T	SL	OWL	741558334	212752	7.5 - 9.5	8.0	10.7	30.5	2,271	13	682
P275/65R18	114T	SL	OWL	741538334	217019	7.5 - 9.5	8.0	11.0	32.1	2,601	13	651
P275/60R20	114T	SL	OWL	741649334	212753	7.5 - 9.5	8.0	11.0	33.0	2,601	13	634

WRANGLER® HT

AN ALL-SEASON TIRE FOR HEAVY-DUTY TRUCKS AND FULL-SIZE VANS.

- Patented, all-season tread design offers year-round traction.
- Circumferential channels offer dependable wet traction.
- Solid center rib offers a smooth ride and long, even wear.



Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Width (ins)	Measuring Rim Width (ins)	Section Width (ins)	Overall Diameter (ins)	Max Load (lbs)	Tread Depth (In 32nds)	Revs/Mile
LT215/75R15	106Q	D	BSL	744154900	182302	5.5 - 7.0	6.0	8.5	27.7	2,095	14	755
LT235/75R15	104Q	C	BSL	744826802	82003	6.0 - 7.0	6.5	9.3	28.9	1,985	14	724
LT215/85R16	115Q	E	BSL	744821900	122771	5.5 - 7.0	6.0	8.6	30.5	2,680	17	688
LT225/75R16	115Q	E	BSL	744830900	139346	6.0 - 7.0	6.0	8.8	29.3	2,680	14	714
LT235/85R16	120R	E	BSL	744725502	88221	6.0 - 7.5	6.5	9.3	31.7	3,042	14	659
LT245/75R16	120R	E	BSL	744395900	163717	6.5 - 8.0	7.0	9.8	30.5	3,042	13	686

NOTES



To learn how Goodyear's industry-leading tires, services and profitability tools help to provide your fleet a total solution, stop by any Goodyear Dealer, or visit goodyeartrucktires.com.



1-866-353-3847 | goodyeartrucktires.com