



ENDURANCE[®] LHS[®] AND LHD

GOODYEAR'S[®] BEST LONG HAUL STEER AND DRIVE COMBINATION FOR MILES TO REMOVAL

ENDURANCE LHS[®]

- NEW WEAR-RESISTANT TREAD COMPOUND for extra-long miles to removal
- NEW DUAL-LAYER TREAD with uniform stiffness for slow, even wear
- NEW RIGID CASING CONSTRUCTION for consistent footprints
- NEW CASING COMPOUNDS for low rolling resistance

Steer



ENDURANCE LHD[®]

- NEW CAP BASE TREAD COMBINATION helps promote longer miles to removal and lower rolling resistance
- NEW CASING COMPOUNDS for low rolling resistance
- STEEL BELT PACKAGE helps provide enhanced casing toughness and durability
- TREDLOCK[®] TECHNOLOGY helps to stabilize tread area for longer miles to removal and resistance to irregular wear

Drive





ENDURANCE LHS AVAILABLE SIZES AND LOAD RANGES

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH		OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH 32NDS	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	MM	IN	MM	IN	MM	IN	MM						
TUBELESS TIRES ON 15" DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	113	51.3	8.25	11.0	279	41.5	1,054	19.4	493	501	311	18	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	114	51.8	8.25	11.0	279	41.5	1,054	19.3	490	501	311	18	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	110	49.8	8.25	11.2	284	40.3	1,024	18.8	478	515	320	18	12.9	328	75	
295/75R22.5	H	7,160	3,250	123	850	6,610	3,000	123	850	110	49.9	8.25	11.3	287	40.4	1,026	18.8	478	515	320	18	12.9	328	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	122	55.4	8.25	12.1	307	43.4	1,102	20.3	516	479	298	18	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	123	55.7	8.25	12.2	310	43.5	1,105	20.4	518	478	297	18	12.5	318	75	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	112	51.0	8.25	12.0	305	41.5	1,054	19.5	495	501	311	18	12.5	318	75	
285/75R24.5	H	6,780	3,075	120	830	6,175	2,800	120	830	113	51.6	8.25	12.1	307	41.6	1,057	19.5	495	499	310	18	12.5	318	75	

Check goodyeartrucktires.com for updated data.



● Recommended



ENDURANCE LHD AVAILABLE SIZES AND LOAD RANGES

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH		OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH 32NDS	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	MM	IN	MM	IN	MM	IN	MM						
TUBELESS TIRES ON 15" DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	126	57	8.25	11.0	279	42.4	1,077	19.9	505	492	306	30	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	126	57	8.25	11.0	279	42.4	1,077	19.9	505	492	306	30	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	129	59	8.25	11.2	284	41.1	1,044	19.3	490	508	316	30	12.9	328	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	140	64	8.25	10.9	277	44.5	1,130	20.9	531	469	291	30	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	140	64	8.25	10.9	277	44.5	1,130	20.9	531	469	291	30	12.5	318	75	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	139	63	8.25	11.1	282	42.3	1,074	19.9	505	493	306	30	12.5	318	75	

Check goodyeartrucktires.com for updated data.



● Recommended ○ Optional

Available Matching UniCircle® Retreads

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
UniCircle	295/75R22.5	8 ½, 9, 9 ¾	215, 230, 235	26
UniCircle	11R22.5	8 ½, 9	215, 230	26
UniCircle	11R24.5	8 ½	215	26



To see how premium Goodyear® tires can help your fleet save money, go to goodyeartrucktires.com.

TOTAL MOBILITY



Trusted Products

Full range of tires, technologies and retreads with options for every fleet.



Premier Service Network

Industry-leading network of 2,300+ North American locations.*



Complete Tire Management

Unparalleled programs and tools to optimize tire assets and ROI.

goodyeartrucktires.com