



## **MORE OUTSTANDING PERFORMANCE IN WASTE HAUL APPLICATIONS**

### ***G289® WHA® DuraSeal™ and Matching G289 UniCircle® & Precure Retreads***

Waste haul vehicles are always put to the test on the job. That's why Goodyear® developed the G289 WHA DuraSeal for a variety of waste haul applications. Plus, haulers can now get the same technology and performance of the G289 WHA DuraSeal from matching UniCircle or precure retreads.

Offering enhanced scrub resistance and tread life, the G289 WHA DuraSeal and retreads help lower operating costs over the life of the casing. This tire is also available without DuraSeal Technology®.



**GOODYEAR**  
MORE DRIVEN.



## G289® WHA® DURASEAL™ FEATURES AND BENEFITS:

- Built-in sealant helps seal tread punctures\* to help keep trucks up and running as well as reduce repair and replacement costs.
- Wider, deeper 24/32" tread helps to extend tread life in waste haul applications.
- Waste haul tread compound helps significantly enhance tread life and scrub resistance.
- Distinct sidewall protector rib helps resist sidewall scuffing in high-scrub waste haul applications to enhance casing life.
- Optimized shoulder design helps direct pressure away from the outer tread to promote uniform treadwear.
- Four wide circumferential grooves help deliver all-season traction on wet, snowy or dry roads in stop/start waste haul applications.
- Wide footprint helps enhance cornering and handling when used on local streets and in transfer stations.

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	160	72	9.00	12.7	323	43.1	1,095	20.0	508	484	301	24	14.0	356	68

### Recommended Tread Design Applications



NON-DURASEAL SIZES AVAILABLE																								
Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			in	mm	32nds	
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	153	69	9.00	12.7	323	43.1	1,095	20.0	508	484	301	24	14.0	356	68



## G289® WHA® RETREAD FEATURES AND BENEFITS:

- Wider, deeper 26/32" tread helps to extend tread life in waste haul applications.
- Waste haul tread compound helps significantly enhance scrub resistance for long tread life.
- Optimized shoulder design helps direct pressure away from the outer tread to promote uniform treadwear.
- Three wide circumferential grooves help deliver all-season traction on wet, snowy or dry roads in stop/start waste haul applications.

Goodyear® UniCircle® Retreads offer spliceless construction for long-lasting treadwear and enhanced resistance to tearing and chunking.

Retreads	Size	Available Width	Tread Depth
		mm	32nds
UniCircle	315/80R22.5	250, 270	26
Precure	-	215, 230, 240, 250, 270, 280	26

### Recommended Tread Design Applications



To learn how Goodyear's industry-leading tires, services and profitability tools help to provide your fleet a total solution, stop by any Goodyear Dealer, or visit [goodyeartrucktires.com](http://goodyeartrucktires.com).



\*Seals up to 1/4" diameter punctures in the repairable area of the tread. Does not seal sidewall punctures.